

Code EAF600SS – 60cm Fixed Rangehood Stainless Steel



FEATURES

- Stainless steel with black front control panel
- 3 speed motor
- 200m³ / hr extraction capacity
- 40W light
- Separate light function
- Recirculating option
- 120mm flue diameter

EXTRACTION CAPACITY

The extraction capacity of 200m³/h

QUIET NOISE LEVEL

A very quiet motor ensures the range hood has a very quiet noise level.

Decibel Rating: 54 dBa

3 SPEED MOTOR

This range hood provides the option of 3 different speed levels ensuring you have the option to use your range hood at a low, medium or high level of operation.

RECIRCULATING OPTION

For installation where the unit can not be vented externally, this rangehood has the ability to recirculate the filtered air back in to the kitchen. A carbon filter can be installed as an optional extra. Carbon Filter Code: CFM001

ELECTRICAL REQUIREMENT:

Range hood is supplied with 10amp cord & plug.

RECIRCULATING ACCESSORIES:

Carbon Filter Code: CFM60FVSS (requires x1)

RANGEHOOD VENTILATION KITS :

RHKE65 – Wall – Eave vent kit

RHKMR65 – Universal metal roof kit, includes flashing

RHKTR65 – Universal tile roof kit, includes flashing

TIPS FOR BETTER USE

- After cooking leave your range hood on for a further 15 minutes to remove fumes
- The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
- It is recommended the range hood be installed between 650mm and 750mm above the cook top
- It is also recommended that exhaust from the range hood be ducted out into the atmosphere
- Turn off the range hood before attempting to clean

- Installation must be through qualified installer.

PRODUCT DIMENSIONS

